

# ROLLER BLIND INSTALLATION (INSIDE THE REVEAL)

## 1. Mount the brackets

Each blind has two brackets – one male bracket for the chain control side of the blind, and one female bracket for the pin end (or non-control end).

Hold the brackets in place, in your window frame where they are to be fixed.

Think about the fall of the blind fabric & position brackets so the blind will miss any handles or latches etc. With a pencil, mark where the two screw holes will go. (2 screws per bracket)

Drill a pilot hole in the middle of each marking with a 2mm drill bit.

Now use the screws provided to fix the brackets securely to the window frame.

## 2. Install the blind

Remove the blind from its packaging, however at this stage, leave the securing band around it's middle.

Slot your blind into the male bracket (chain side first).

Ensure that the chain hangs down freely and the ends of the guarded part are level across the top.

Remove the securing band from the blind.

Hold the chain-side in position and move to the other side of the blind.

Retract the metal spring loaded pin slightly by turning the grooved plastic wheel – Then guide the pin up into the track of the female bracket until it clicks into position.

## 3. Connect the chain-stopper

Your blind is now installed – it can now be lowered using the chain control. Once fully lowered, place the supplied plastic chain stopper on the control chain where it enters the chain drive.

**TIP: Front rolling blinds** need the chain stopper where the chain enters at the back.

**Back rolling blinds** need the chain stopper where the chain enters at the front.

Chain stoppers (one per blind) prevent the blind from being rolled down too far. You may need to adjust the position of this chain stopper and test to get the best placement.